

GRIPlag 50

**For drive pulley systems
Smooth, Diamond
Non-Marking**



GRIPlag 50 is a natural rubber blend with a high coefficient of friction for drive pulley systems. Available with a smooth or omni directional diamond profile surface (GRIPlag 50) and bonding layer for vulcanization to metal.

GRIPlag 50 is used on drive tail or blend pulleys in damp or wet conditions where maximum traction is needed to reduce slippage of conveyor belts. GRIPlag 50 is very resilient to caking and build up on pulleys is not a problem on light and medium tension conveyor systems. GRIPlag 50 diamond profiled lagging will dissipate water and dirt in all directions. NON MAGRIPlag 50 is also available with the omni directional diamond profile. It is designed where non marking features are required.

1 Thickness specification
follows MIL--3065E

1/8" ± .020 3/4" ± .093
1/4" ± .031 1" ± .100

PROPERTIES

Polymer:

Color:

Hardness:

Tensile strength:

Elongation at break:

NR/SBR

Blue

50° duro scale shore "A" ± 5°

1,800 psi (12.3 MPa)

500%

STORAGE

Store rubber products, cements and solvents
in a cool, dry, dark place. Avoid direct sunlight.



Call Green Rubber - Kennedy Ag for recommendations
on rubber type, thickness, and other specifications
to perform best in your applications.

(831) 753-6100

sales@greenrubber.com

www.greenrubber.com