

WATER STORAGE SOLUTIONS

Your headquarters for tanks, pumps, hose, valves & fittings

TANKS APPROVED FOR DRINKING WATER

	otal Illons	Model	Weight	Diameter	Height	Price
15	5,500	15000	3,000	12 ft.	20 ft.	\$17,500
10	0,000	9800	1,800	12 ft.	13 ft. 6 in.	\$10,300
8	,000	8000	1,650	10 ft.	15 ft.	\$7,175
6	,500	6500	1,500	10 ft.	12 ft. 6 in.	\$5,200
5	,400	4900	800	12 ft.	7 ft. 6 in.	\$3,650
5	,100	4910	825	10 ft.	9 ft. 6 in.	\$3,650
4	,925	4925	1,000	8 ft. 5 in.	12 ft. 8 in.	\$4,250
3	,000	3000	440	8 ft.	9 ft. 8 in.	\$2,325
2	,650	2600	440	8 ft.	8 ft. 6 in.	\$1,850
1	,600	1500	320	7 ft. 2 in.	6 ft.	\$1,340
1	,350	1100	220	7 ft. 2 in.	4 ft. 5 in.	\$1,165
1	,075	1000	335	5 ft.	8 ft.	\$1,250
	725	685	140	5 ft.	5 ft.	\$925
	550	550	140	5 ft. 4 in.	4 ft. 5 in.	\$775
!	500	500	140	4 ft.	6 ft.	\$775
	340	330	75	47 in.	49 in.	\$495
	205	205	62	42 in.	43 in.	\$450



SEPTIC & CISTERN TANKS

Total Gallons	Length	Width	Height	Number of Manholes	Price
300 Sphere	48.5 in.	48.5 in.	53 in.	1 - 20 in.	\$875
500 Sphere	60 in.	60 in.	63 in.	1 - 20 in.	\$1,100
500 Lo Profile	88 in.	48 in.	42 in.	1 - 20 in.	\$1,195
1000 NexGen*	127 in.	60 in.	51 in.	2 - 20 in	\$1,860
1500 NexGen*	157 in.	60 in.	51 in.	2 - 20 in.	\$2,775
1175 Cistern	127 in.	60 in.	51 in.	2 - 20 in.	\$1,925
1725 Cistern	157 in.	69 in.	51 in.	2 - 20 in.	\$2,850
2500 Cistern	159 in.	99 in.	51 in.	2 - 20 in.	\$4,800
3525 Cistern	211 in.	102 in.	51 in.	2 - 20 in.	\$7,600

^{*} Double compartment septic tanks - plumbing included. IAPMO approved



Prices effective May 31, 2021 Subject to change

WATER STORAGE SOLUTIONS



ABOVE-GROUND PLASTIC TANKS

- Long-term outdoor service with UV stabilized materials
- Manufactured with FDA approved resin for potable water
- Comes standard with 2" bolted drain fitting and 1/2" bulkhead float valve fitting
- Weatherproof threaded lids & anti-static surge vents
- Molded-in gallon scale (most tanks)
- Offset fill-wells

SEPTIC & CISTERN TANKS

- Rugged, rotation-molded, one-piece, seamless tanks
- Ribbed construction for superior structural strength
- For underground installations
 6" to 36" deep
- Designed for installation below surface, only in areas with no vehicle traffic

HIGH CAPACITY STEEL TANKS

- From 5,000 to 100,000 gallon storage capacities
- Modular construction for sites with limited access
- Fire-safe, with highest UV and corrosion resistance
- For drinking water and fire protection applications
- Higher vol. per sq. ft. than interconnected sytems
- Optional rainwater collector
- Special geosynthetic liners



Your headquarters for tanks, pumps, hoses, valves & fittings

